



TOPTAWA

TOPTAWA: *THREE PHASE PHASE CONTROL*

Maden in TaiWan

| | | | | | | | | | | | | | | | | | | | | |
|--|---|---|---|---|---|---|---|---|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|
|  |  |  |  |  |  |  |  |  | | | | | | | | | | | | |
| Model No. | TMPT 0202 | TMPT 0204 | TMPT0 302 | TMPT0 304 | TMPT 0502 | TMPT 0504 | TMPT 0702 | TMPT 704 | TMPT 1002 | TMPT 1004 | TMPT 1202 | TMPT 1204 | TMPT 1602 | TMPT 1604 | TMPT 2002 | TMPT 2004 | TMPT 2502 | TMPT 2504 | TMPT 3002 | TMPT 3004 |
| Load Current Rating | 20A | | 30A | | 50A | | 70A | | 100A | | 120A | | 160A | | 200A | | 250A | | 300A | |
| Load Voltage | 150~ 260V | 240V~ 500V | 150~ 280V | 240V~ 500V | 150~ 260V | 240~ 500V | 150~ 280V | 240~ 500V | 150~ 260V | 240~ 500V | 150~ 280V | 240~ 500V | 150~ 260V | 240~ 500V | 150~ 280V | 240~ 500V | 150~ 260V | 240~ 500V | 150~ 280V | 240~ 500V |
| L. s. wall (mm) | 5x128x115 | | 5x110x115 | | 133x128x170 | | 175x128x170 | | 208x140x200 | | | | 350x140x200 | | | | 488x140x200 | | | |
| Weight (g) | 1500 | | 2500 | | 4800 | | | | 5300 | | | | 9400 | | | | 10500 | | | |
| auxiliary Power | 88-264 (50Hz or 60Hz) | | | | | | | | | | | | | | | | | | | |
| Min Load | 0.6A | | | | | | | | | | | | | | | | | | | |
| Off state Leakage Current | 8ma under (R. C FILTER) | | | | | | | | | | | | | | | | | | | |
| Power | 3.2w (Max) | | | | | | | | | | | | | | | | | | | |
| Frequency Range | 50Hz or 60Hz ±5% | | | | | | | | | | | | | | | | | | | |
| Control | DCA (4-20mA, 0-20ma) . DCV (0-5V, 1-5V, 2-10V, 0-10V) | | | | | | | | | | | | | | | | | | | |
| Input | DCA (250 Ω) DCV (4.7K Ω or 10K Ω) | | | | | | | | | | | | | | | | | | | |
| Isolation Voltage | AC2000V (1 MIN) | | | | | | | | | | | | | | | | | | | |

32/1 หมู่ 3 ตำบลป่าตัน อำเภอแม่อิง จังหวัดลำปาง 52150, 32/1, Moo 3, Patan, Maetha, Lampang, Thailand 52150, Tel. (Sales): 085-0886601
 Tel: +66(0)54-289-289 Fax: +66(0)54-289-368. <http://www.furnacedesigns.com> E-mail: furnacedesigns@hotmail.com

TOPTAWA

TOPTAWA: THREE PHASE TIME BASE ZERO CONTROL

Maden in TaiWan

| | | | | | | | | | | | | | | | | | | | | |
|--|---|---|---|---|--|---|---|---|---|---------------|--------------|---------------|--------------|---------------|--------------|---------------|--------------|---------------|--------------|---------------|
|  |  |  |  |  |  |  |  |  |  | | | | | | | | | | | |
| Model No. | ETV202 | ETV204 | ETD302 | ETD304 | ETD502 | ETD504 | ETD702 | ETD704 | ETD1002 | ETD1004 | ETD1202 | ETD1204 | ETD1502 | ETD1504 | ETD2002 | ETD2004 | ETD2502 | ETD2504 | ETD3002 | ETD3004 |
| Load Current Rating | 20A | | 30A | | 50A | | 70A | | 100A | | 120A | | 150A | | 200A | | 250A | | 300A | |
| Load Voltage | 150~ 260V | 240V~ 500V | 150~ 260V | 240V~ 500V | 150~ 260V | 240V~ 500V | 150~ 260V | 240V~ 500V | 150~ 260V | 240V~ 500V | 150~ 260V | 240V~ 500V | 150~ 260V | 240V~ 500V | 150~ 260V | 240V~ 500V | 150~ 260V | 240V~ 500V | 150~ 260V | 240V~ 500V |
| L. s. wall (mm) | 5x126x115 | | 5x110x115 | | 133x126x170 | | 175x126x170 | | 208x140x200 | | | | 360x140x200 | | | | 468x140x200 | | | |
| Weight (g) | 700 | | 1350 | | 1900 | | 2500 | | 4800 | | | | 7000 | | | | 9400 | | | |
| auxiliary Power | 88-264 (50Hz or 60Hz) | | | | | | | | | | | | | | | | | | | |
| Min Load | 0.6A | | | | | | | | | | | | | | | | | | | |
| Off state Leakage Current | 8mA under (R. C FILTER) | | | | | | | | | | | | | | | | | | | |
| Power | 3.2w (Max) | | | | | | | | | | | | | | | | | | | |
| Frequency Range | 50Hz or 60Hz ±5% | | | | | | | | | | | | | | | | | | | |
| Control | DCA (4-20mA, 0-20mA) . DCV (0-5V, 1-5V, 2-10V, 0-10V) | | | | | | | | | | | | | | | | | | | |
| Input | DCA (250Ω) DCV (4.7KΩ or 10KΩ) | | | | | | | | | | | | | | | | | | | |
| Isolation Voltage | AC2000V (1 MIN) | | | | | | | | | | | | | | | | | | | |